

ABSOLUTE
LEVEL

BACKLIGHT

BUILT-IN
BLUETOOTH

BUILT-IN BLUETOOTH DIGITAL LEVELS AND SLOPE METERS

WORKING TEMPERATURE
0°C~50°C




VIDEO

both angle and
slope are displayed





4910-400WL



4910-600WL

- With transverse and longitudinal vials
- Used as level and slope meter
- Aluminum frame, magnetic bottom
- The sea level is permanently set inside the chip, zero setting is not needed when batteries are replaced
- Buttons: ON/OFF, absolute and incremental measurement, keep the reading, buzzer alarm (not for 4910-400WL), unit (mm/m, %, in/ft), conversion (not for 4910-400WL), backlight
- The display flips over when the bottom faces up
- Built-in Bluetooth, transmission distance is 10 meters (under the condition of no obstruction and no electromagnetic interference)
- Android and iPhone APP are included
- Two AAA batteries
- Automatic power off

Android and iPhone APP (included)
can choose real-time display (continuous transmission) or single transmission



(mm)

Code	Range	Resolution	Accuracy	Remark*	L	L1	a	b
4910-400WL	0~360° (90°×4)	angle: 0.1°	±0.2°	both angle and slope are displayed (slope is calculated by angle)	416	400	50	21
4910-600WL	0~360° (90°×4)	at 0° and 90°: 0.05°; at others: 0.1°	at 0° and 90°: ±0.1°; at others: ±0.2°	at 0° and 90° buzzer alarm	600	585	60	25
4910-1000WL	0~360° (90°×4)	at 0° and 90°: 0.05°; at others: 0.1°	at 0° and 90°: ±0.1°; at others: ±0.2°	at 0° and 90° buzzer alarm	1000	984	60	25

* mm/m=tan(°)×1000, for example: 0.3°=tan(0.3)×1000=5mm/m