

NON-ROTATING
SPINDLE

DATA
OUTPUT







3583-25A

- Resolution 0.001mm/0.00005"
- Non-rotating spindle
- Button function: on/off, set, mm/inch, data transmit
- Data output
- Automatic power off
- Ratchet stop
- Supplied with setting standards (except 0-25mm/0-1")
- Power:
with data interface: CR2032
built-in wireless: rechargeable lithium battery

With data interface (optional data output cable:
code 7315-31 receiver is needed, 7302-31)

Code	Range	Accuracy	L	a	b	c	R	D
3583-25A	0-25mm/0-1"	±4μm	43	6.5	32	5	10	8
3583-50A	25-50mm/1-2"	±4μm	85	6.5	44.5	5	10	8
3583-75A	50-75mm/2-3"	±5μm	110	6.5	57	5	10	8
3583-100A	75-100mm/3-4"	±5μm	135	6.5	70	5	10	8
3583-125A	100-125mm/4-5"	±6μm	160	11.5	86	8	15	12
3583-150A	125-150mm/5-6"	±6μm	186	11.5	94.5	8	15	12
3583-175A	150-175mm/6-7"	±7μm	211	11.5	107	8	15	12
3583-200A	175-200mm/7-8"	±7μm	236	11.5	120	8	15	12

DIGITAL JAW TYPE MICROMETERS



Built-in wireless (receiver
code 7315-2/3/6/7/8/9 is needed)

Code

3583-□□□□WL

Code examples:

Original code	Wireless code
3583-25A	3583-25AWL
3583-50A	3583-50AWL